



- ELECTRICAL NOTES**
1. NOT MORE THAN TEN (10) CONDUITS PER OUTLET SHALL BE PERMITTED ON ANY 20' x 24' CREDIT WAIN, ICE AND WRELS.
  2. WHERE THE SERVICE CONDUIT IS EXTENDED TO PERFORM A JOB OF NOT LESS THAN 18" TRAYS SHALL BE USED. THE LAST TRAY SHALL NOT EXCEED MORE THAN 50' BEYOND THE SUBSTANTIAL SERVICE EQUIPMENT SHALL BE PROTECTED BY CONDUIT. USE AN EIGHT (8) INCH TRAY WHEN THE TRAY HAS MORE THAN 6" CLEARANCE FROM THE WALLS TO BE INSTALLED.
  3. ON EXPOSED & UNPROTECTED ALL CROCKETS SHALL BE PROTECTED BY CONDUIT. ALL EXPOSED CROCKETS SHALL BE PROTECTED BY CONDUIT. ALL EXPOSED CROCKETS SHALL BE PROTECTED BY CONDUIT. ALL EXPOSED CROCKETS SHALL BE PROTECTED BY CONDUIT.
  4. ALL NEW ELECTRICAL WORK SHALL COMPLY WITH NEC, ETC STANDARDS. PLACE NEW ELECTRICAL FITTINGS ON NEW CONDUIT. USE AN EIGHT (8) INCH TRAY WHEN THE TRAY HAS MORE THAN 6" CLEARANCE FROM THE WALLS TO BE INSTALLED. HAVE WRELS & CONDUIT FOR ELECTRICAL STANDARDS TO BE INSTALLED.
  5. NEW 15, 20, 30 AMP RECEPTACLE OUTLET BOXES SHALL BE INSTALLED NOT LESS THAN 18" ABOVE THE FRESH FLOOR FINISH.
  6. LOCATE THE CENTER OF NEW SWITCHES 10' LESS THAN 24" & 10' MORE THAN 48" ABOVE THE FRESH FLOOR FINISH. LOCATE THE CENTER OF NEW SWITCHES 10' LESS THAN 24" & 10' MORE THAN 48" ABOVE THE FRESH FLOOR FINISH.
  7. LOCATE THE CENTER OF NEW SWITCHES 10' LESS THAN 24" & 10' MORE THAN 48" ABOVE THE FRESH FLOOR FINISH.
  8. COORDINATE ELECTRICAL WORK WITH MECHANICAL & ALL OTHER SUB-CONTRACTORS.
  9. ALL NEW ELECTRICAL WORK SHALL BE INSTALLED IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE (NEC) AND ALL OTHER APPLICABLE CODES.
  10. THE TOP OF SWITCH BOXES, THERMOSTATS AND DIMMER CONTROLS SHALL BE A MINIMUM OF 48" AFF - TYPICAL.
  11. THE BOTTOM OF RECEPTACLE BOXES SHALL BE A MINIMUM OF 18" ABOVE FRESH FLOOR (AFF) - TYPICAL.
  12. ALL ELECTRICAL WORK SHALL BE INSTALLED IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE (NEC) AND ALL OTHER APPLICABLE CODES.
  13. ALL ELECTRICAL WORK SHALL BE INSTALLED IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE (NEC) AND ALL OTHER APPLICABLE CODES.
  14. ALL ELECTRICAL WORK SHALL BE INSTALLED IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE (NEC) AND ALL OTHER APPLICABLE CODES.
  15. ALL ELECTRICAL WORK SHALL BE INSTALLED IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE (NEC) AND ALL OTHER APPLICABLE CODES.
  16. ALL ELECTRICAL WORK SHALL BE INSTALLED IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE (NEC) AND ALL OTHER APPLICABLE CODES.
  17. ALL ELECTRICAL WORK SHALL BE INSTALLED IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE (NEC) AND ALL OTHER APPLICABLE CODES.
  18. ALL ELECTRICAL WORK SHALL BE INSTALLED IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE (NEC) AND ALL OTHER APPLICABLE CODES.
  19. ALL ELECTRICAL WORK SHALL BE INSTALLED IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE (NEC) AND ALL OTHER APPLICABLE CODES.
  20. ALL ELECTRICAL WORK SHALL BE INSTALLED IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE (NEC) AND ALL OTHER APPLICABLE CODES.

